

SAFETY DATA SHEET

***** SECTION I – IDENTIFICATION *****

MANUFACTURER NAME

Mullen Circle Brand, Inc.
3514 West Touhy Avenue
Skokie, Illinois 60076

PHONE NUMBER

847/676-1880

EMERGENCY CONTACT

800/535-5053

PRODUCT NAME

Adams Elevator
Contact Cement
Part# APC130CC-CASE

RECOMMENDED USE

Adhesive

E-Mail

SDS@MullenOil.com

RESTRICTIONS ON USE

It is against federal law to use this product inconsistent with its labeling

***** SECTION II – HAZARD(S) IDENTIFICATION *****

OSHA Status

Hazardous

GHS HAZARD CLASS**Physical Hazards**

Flammable liquid – Category 2

Health Hazards

Acute toxicity – Category 4 (Inhalation)

Acute toxicity – Category 4 (Oral)

Carcinogenicity – Category 1b

Serious eye damage/eye irritation – Category 2

Mutagenicity – Category 1b

Skin corrosion/irritation – Category 2

Specific target organ effects, single exposure – Category 3 (Narcotic effects)

Specific target organ effects, single exposure – Category 3

(Respiratory tract irritation)

Specific target organ effects, repeated exposure - Category 2

Environmental Hazards Not classified

GHS Symbol/Pictogram**Signal Word**

Danger

Hazard Statements

Highly flammable liquid & vapor
Harmful if swallowed
Causes skin irritation
Causes serious eye irritation
Harmful if inhaled
May cause respiratory irritation
May cause drowsiness or dizziness

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

***** SECTION II – HAZARD(S) IDENTIFICATION (Continued) *****

Hazard Statements (continued): May cause genetic defects
May cause cancer
May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
Do not eat, drink or smoke when using this product
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Do not spray on an open flame or other ignition source
Pressurized container, do not pierce or burn, even after use
Take precautionary measures against static discharge
Avoid breathing dust, fumes, gas, mist, vapors, spray
Wash thoroughly after handling
Use only outdoors or in a well ventilated area
Wear protective gloves, protective clothing, eye protection, face protection
Obtain special instructions before use. Do not handle until all safety precautions
Have been read and understood

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
Do not induce vomiting
IF ON SKIN: Wash with plenty of water
IF ON SKIN (or hair): Remove contaminated clothing. Rinse skin with water
If skin irritation occurs, get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
lenses if present and easy to do. Continue rinsing.
If eye irritation persists, get medical advice/attention
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER/doctor/physician if you feel unwell
Avoid contact during pregnancy and while nursing
Specific treatment (see first aid section)
In case of fire: Use foam, CO2, dry chemical

Storage

Store in a well ventilated place. Keep container closed when not in use
Keep cool. Do not expose to temperatures above 122 F.
Store locked up

Disposal

Dispose of contents/container in accordance with local/state/federal regulations
Avoid release to the environment

***** SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS *****

Substance _____ **Mixture** X

Chemical Name	CAS#	%
Toluene	108-88-3	50-75
Methyl Ethyl Ketone	78-93-3	10-25
Light aliphatic solvent naphtha	64742-89-8	2.5-10
n-Heptane	142-82-5	2.5-10
Magnesium oxide fume	1309-48-4	1.0-2.5

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

***** **SECTION IV – FIRST AID MEASURES** *****

Description Of Necessary First Aid Measures

Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

***** **SECTION V – FIREFIGHTING MEASURES** *****

Extinguishing Media

Suitable

Foam, CO2, dry chemicals, water fog or mist.

Unsuitable

Do not use water jet.

Specific Hazards

Flammable liquid and vapor. Contents under pressure. Pressurized container may explode when exposed to heat or flame. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous Decomposition Products

Oxides of carbon, sulfur.

Special Precautions – Fire Fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if it can be done without risk. No action shall be taken involving any personal risk or without suitable training.

Special Protective Equipment – Fire Fighters

Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

******* SECTION VI – ACCIDENTAL RELEASE MEASURES *******

Personal Precautions, Protective Equipment And Emergency Procedures

For Non-Emergency Personnel

Take no action involving personal risk without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery, use care to avoid falling.

For Emergency Responders

If specialized clothing is required to deal with the spillage, take note of any information in Section VIII on suitable and unsuitable materials. See also the information in “For Non-Emergency Personnel”.

Environmental Precautions

Avoid dispersal of spilled products and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product causes environmental pollution.

Methods And Materials For Containment And Cleaning Up

Small Spill

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spill

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

******* SECTION VII – HANDLING & STORAGE *******

Precautions For Safe Handling

Protective Measures

Put on appropriate personal protective equipment (See Section VIII). Do not swallow. Avoid contact with eyes, skin, clothing. Avoid breathing vapor and mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Always bond receiving containers to the fill pipe before and during loading. Always confirm receiving container is properly grounded.

Advice On General Occupational Hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section VIII for additional information on hygiene measures.

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

******* SECTION VII – HANDLING & STORAGE (Continued) *******

Conditions For Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section X) and food and drink. Keep away from heat, sparks and open flame. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

******* SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION *******

Exposure Limits

Ingredient Name	Exposure Limits	
n-Heptane	OSHA PEL-TWA	500 ppm; 2000 mg/cubic meter
	ACGIH TLV-STEL	500 ppm
	ACGIH TLV-TWA	400 ppm
	NIOSH REL-Ceiling	440 ppm; 1800 mg/cubic meter
	NIOSH REL-TWA	85 ppm; 350 mg/cubic meter
Toluene	OSHA PEL-Ceiling	300 ppm
	OSHA PEL-TWA	200 ppm
	ACGIH TLV-TWA	20 ppm
	NIOSH REL-STEL	1500 ppm; 560 mg/cubic meter
	NIOSH REL-TWA	100 ppm; 375 mg/cubic meter
Methyl Ethyl Ketone	ACGIH TLV-TWA	200 ppm
	ACGIH TLV-STEL	300 ppm
	OSHA PEL-TWA	200 ppm; 590 mg/cubic meter
	OSHA PEL-Ceiling	Not Established
Magnesium oxide fume	ACGIH TLV-TWA	10 mg/cubic meter
	OSHA PEL-TWA	15 mg/cubic meter

Environmental Exposure Controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

Hygiene Measures

Wash hands, forearms and face thoroughly after handling chemical products and before eating, smoking or using the lavatory as well as at the end of the work period. Wash contaminated clothing before reusing.

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

******* SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION (Continued) *******

Respiratory Protection

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Eye Protection

Safety glasses equipped with side shields in conjunction with a face shield are recommended in industrial settings.

Skin Protection

Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

******* SECTION IX – PHYSICAL & CHEMICAL PROPERTIES *******

Appearance

Physical State	Liquid
Color	Tan

Odor	Strong solvent
Odor Threshold	Not available

Ph	None
Melting Point	Not available
Freezing Point (Pour Point)	Not available

Drop Point	Not applicable
Flash Point	-6.1 C (Seta closed cup)

Evaporation Rate	Faster than n-butyl acetate
-------------------------	-----------------------------

Vapor Pressure	Not available
Vapor Density	Heavier than air

Specific Gravity	.88
Solubility	Insoluble in water

Boiling Range	76.7-82.2 C
----------------------	-------------

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

******* SECTION X – STABILITY & REACTIVITY**

Reactivity

Bulk product not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS definitions

Chemical Stability

This product is stable under normal conditions.

Possibility Of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions To Avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible Materials

Reactive or incompatible with the following materials: Oxidizing materials.

Hazardous Decomposition Products

Oxides of carbon and sulfur.

******* SECTION XI – TOXICOLOGICAL INFORMATION *******

Primary Routes Of Exposure:

Eye contact, Ingestion, Inhalation, Skin contact

Acute Toxicity Values:

Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Information On Toxicological Effects - Effects Of Overexposure

Inhalation

Vapors can cause irritation of the nose, throat, lungs and respiratory tract. High concentrations can cause shortness of breath, headache, nausea, weakness, lightheadedness, and stupor (CNS depression). Causes delayed lung injury.

Skin Contact

Causes skin irritation. Can be absorbed through the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

Eye Contact

Contact with the eye causes serious irritation. May cause tearing, redness and discomfort.

Ingestion

Harmful or fatal if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause gastrointestinal disturbances with dizziness and central nervous system depression. If ingested, may cause depressed respiration. Aspiration hazard if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

******* SECTION XI – TOXICOLOGICAL INFORMATION *******

Sensitization	
Respiratory	Not classified
Skin Sensitization	Not classified
Germ Cell Mutagenicity	Mutagenicity – Category 1b
Carcinogenicity	Carcinogenicity – Category 1b
Fertility Effects	Not classified
Specific Target Organ Toxicity	
Single Exposure	Category 3 - Narcotic effects/Respiratory tract irritation
Repeated Exposure	Category 2 - May cause damage to organs through prolonged or repeated exposure
Aspiration Hazard	Not classified

******* SECTION XII – ECOLOGICAL INFORMATION *******

Ecotoxicity
Not available

Persistence & Degradability
Not available

Bioaccumulative Potential
Not available

Mobility In Soil
Not available

Other Adverse Effects
No known significant effects or critical hazards.

******* SECTION XIII – DISPOSAL CONSIDERATIONS *******

Disposal Methods
Waste generation should be avoided or minimized wherever possible. Dispose of in accordance with federal, state, and local regulations. After the container has been emptied, it may contain hazardous residues. Avoid sparks and open flame. Do not cut, puncture, or weld on or near the container. Do not reuse the container for any purpose until properly reconditioned.

RCRA Classification
Hazardous Waste

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Contact Cement
Part# APC130CC-CASE

***** SECTION XIV – TRANSPORT INFORMATION *****

DOT

UN# UN1133
UN SHIPPING NAME Adhesives, containing a flammable liquid
Transport Hazard class Class 3
Packing Group III

***** SECTION XV – REGULATORY INFORMATION *****

TSCA Section 12(b) Export notification (40 CFR 707 Subpart D): None

CERCLA Hazardous Substance List (40 CFR 302.4): Toluene

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed

SARA Section 302 – Threshold Planning Quantity : None

SARA Title III – Section 311/312

Immediate/Acute Health Effects : Yes
Fire Hazard : Yes
Delayed/Chronic Health Effects : Yes
Reactivity Hazard : No
Sudden Release Of Pressure Hazard : No

Chemical Release Reporting:

SARA Section 313 : Toluene
CERCLA : Not listed

TSCA Inventory : All product ingredients are listed on the chemical inventory.

Clean Air Act

Section 112 Hazardous Air Pollutants : Toluene

***** SECTION XVI – OTHER INFORMATION *****

The above mentioned information is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition the person receiving it shall make his own determination as to the suitability of the material for his particular use and on the condition he assume the risk of his use thereof.

Revision Date: August 1, 2016