

SAFETY DATA SHEET

***** SECTION I – IDENTIFICATION *****

MANUFACTURER NAME

Mullen Circle Brand, Inc.
3514 West Touhy Avenue
Skokie, Illinois 60076

PHONE NUMBER

847/676-1880

EMERGENCY CONTACT

800/535-5053

PRODUCT NAME

Adams Elevator
Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

RECOMMENDED USE

Lubricant

E-Mail

SDS@MullenOil.com

RESTRICTIONS ON USE

It is against federal law to use this product inconsistent with its labeling

***** SECTION II – HAZARD(S) IDENTIFICATION *****

OSHA Status

Hazardous

GHS HAZARD CLASS**Physical Hazards**

Flammable Aerosols – Category 2

Health Hazards

Skin corrosion/ irritation –Category 2
Serious eye damage/irritation – Category 2A
Specific target organ toxicity, single exposure – Category 3 (Narcotic effects)
Aspiration hazard – Category 1

Environmental Hazards Not classified

GHS Symbol/Pictogram**Signal Word**

Danger

Hazard Statements

Flammable aerosol
Causes serious eye irritation
Causes skin irritation
May cause drowsiness or dizziness
May be fatal if swallowed & enters airways

PRODUCT NAME

Mullen Circle Brand, Inc.
 Adams Elevator Waterproof Grease - Aerosol
 Part# APA100CC-CASE, APA100S

***** SECTION II – HAZARD(S) IDENTIFICATION (Continued) *****
--

Precautionary Statements**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 Do not eat, drink or smoke when using this product
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment
 Use only non-sparking tools
 Do not spray on an open flame or other ignition source
 Pressurized container, do not pierce or burn, even after use
 Take precautionary measures against static discharge
 Avoid breathing dust, fumes, gas, mist, vapors, spray
 Wash thoroughly after handling
 Use only outdoors or in a well ventilated area
 Wear protective gloves, protective clothing, eye protection, face protection
 Obtain special instructions before use. Do not handle until all safety precautions
 Have been read and understood

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
 Do not induce vomiting
 IF ON SKIN: Wash with plenty of water
 IF ON SKIN (or hair): Remove contaminated clothing. Rinse skin with water
 If skin irritation occurs, get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
 lenses if present and easy to do. Continue rinsing.
 If eye irritation persists, get medical advice/attention
 IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Call a POISON CENTER/doctor/physician if you feel unwell
 Avoid contact during pregnancy and while nursing
 Specific treatment (see first aid section)
 In case of fire: Use foam, CO2, dry chemical

Storage

Store in a well ventilated place. Keep container closed when not in use
 Keep cool. Do not expose to temperatures above 122 F.
 Store locked up

Disposal

Dispose of contents/container in accordance with local/state/federal regulations
 Avoid release to the environment

***** SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS *****

Substance _____ **Mixture** X

Chemical Name	CAS#	%
Acetone	67-64-1	10-30
Butane	106-97-8	9-14
Propane	74-98-6	10-15
Naphtha (petroleum), Hydrotreated light	64742-49-0	15-40

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

***** **SECTION IV – FIRST AID MEASURES** *****

Description Of Necessary First Aid Measures

Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

***** **SECTION V – FIREFIGHTING MEASURES** *****

Extinguishing Media

Suitable

Foam, CO2, dry chemicals, water fog or mist.

Unsuitable

Do not use water jet.

Specific Hazards

Flammable liquid and vapor. Contents under pressure. Pressurized container may explode when exposed to heat or flame. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous Decomposition Products

Oxides of carbon, sulfur.

Special Precautions – Fire Fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if it can be done without risk. No action shall be taken involving any personal risk or without suitable training.

Special Protective Equipment – Fire Fighters

Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

******* SECTION VI – ACCIDENTAL RELEASE MEASURES *******

Personal Precautions, Protective Equipment And Emergency Procedures

For Non-Emergency Personnel

Take no action involving personal risk without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery, use care to avoid falling.

For Emergency Responders

If specialized clothing is required to deal with the spillage, take note of any information in Section VIII on suitable and unsuitable materials. See also the information in “For Non-Emergency Personnel”.

Environmental Precautions

Avoid dispersal of spilled products and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product causes environmental pollution.

Methods And Materials For Containment And Cleaning Up

Small Spill

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spill

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

******* SECTION VII – HANDLING & STORAGE *******

Precautions For Safe Handling

Protective Measures

Put on appropriate personal protective equipment (See Section VIII). Do not swallow. Avoid contact with eyes, skin, clothing. Avoid breathing vapor and mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Always bond receiving containers to the fill pipe before and during loading. Always confirm receiving container is properly grounded.

Advice On General Occupational Hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section VIII for additional information on hygiene measures.

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

******* SECTION VII – HANDLING & STORAGE (Continued) *******

Conditions For Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section X) and food and drink. Keep away from heat, sparks and open flame. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

******* SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION *******

Exposure Limits

Ingredient Name	Exposure Limits	
Acetone	OSHA PEL-TWA	1000 ppm; 2400 mg/cubic meter
	ACGIH TLV-STEL	750 ppm; 1782 mg/cubic meter
	ACGIH TLV-TWA	500 ppm; 1188 mg/cubic meter
	NIOSH REL-TWA	250 ppm; 590 mg/cubic meter
Propane	OSHA PEL-TWA	1000 ppm; 1800 mg/cubic meter
	NIOSH TLV-TWA	1000 ppm; 1800 mg/cubic meter
Butane	NIOSH REL-TWA	800 ppm; 1900 mg/cubic meter
	ACGIH TLV-STEL	1000 ppm

Environmental Exposure Controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

Hygiene Measures

Wash hands, forearms and face thoroughly after handling chemical products and before eating, smoking or using the lavatory as well as at the end of the work period. Wash contaminated clothing before reusing.

Respiratory Protection

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Eye Protection

Safety glasses equipped with side shields in conjunction with a face shield are recommended in industrial settings.

Skin Protection

Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

******* SECTION IX – PHYSICAL & CHEMICAL PROPERTIES *******

Appearance	
Form	Aerosol
Physical State	Gas
Color	Clear
Odor	Mild solvent
Odor Threshold	Not available
Ph	None
Drop Point	Not applicable
Flash Point	-156.00 F Propellant
Evaporation Rate	<1 (butyl acetate=1)
Viscosity	NLGI 2
Vapor Pressure	>0.13 kPa @ 70 F
Vapor Density	>1 (air=1)
Specific Gravity	<.1.0
Solubility	Insoluble in water
Flammable Limits	
Upper	13%
Lower	1%

******* SECTION X – STABILITY & REACTIVITY *******

Reactivity

Bulk product not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS definitions

Chemical Stability

This product is stable under normal conditions.

Possibility Of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions To Avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible Materials

Reactive or incompatible with the following materials: Oxidizing materials.

Hazardous Decomposition Products

Oxides of carbon and sulfur.

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

******* SECTION XI – TOXICOLOGICAL INFORMATION *******

Primary Routes Of Exposure: Eye contact, Ingestion, Inhalation, Skin contact

Acute Toxicity Values: Not acutely toxic

Information On Toxicological Effects - Effects Of Overexposure

- Inhalation** Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). Causes delayed lung injury.
- Skin Contact** Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.
- Eye Contact** Contact with the eye causes serious irritation. May cause tearing, redness and discomfort.
- Ingestion** Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach. As this product is a gas, refer to the inhalation section.
- Chronic Hazards** Possible brain damage from overexposure. Overexposure may cause nervous system damage.
- Sensitization**
 - Respiratory** Not classified
 - Skin Sensitization** Not classified
- Germ Cell Mutagenicity** Non-mutagenic based on a Modified Ames Assay.
- Carcinogenicity** Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346. This product is not listed as a carcinogen by IARC, OSHA, NTP.
- Fertility Effects** Not classified
- Specific Target Organ Toxicity**
 - Single Exposure** Category 3 - Narcotic effects
 - Repeated Exposure** Not classified
- Aspiration Hazard** Category 1 - May be fatal if swallowed and enters airways

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

***** SECTION XII – ECOLOGICAL INFORMATION *****

Ecotoxicity
Not available

Persistence & Degradability
Not available

Bioaccumulative Potential
Not available

Mobility In Soil
Not available

Other Adverse Effects
No known significant effects or critical hazards.

***** SECTION XIII – DISPOSAL CONSIDERATIONS *****

Disposal Methods
Waste generation should be avoided or minimized wherever possible. Dispose of in accordance with federal, state, and local regulations. After the container has been emptied, it may contain hazardous residues. Avoid sparks and open flame. Do not cut, puncture, or weld on or near the container. Do not reuse the container for any purpose until properly reconditioned.

RCRA Classification
Hazardous Waste

***** SECTION XIV – TRANSPORT INFORMATION *****

DOT

UN#	UN1950
UN SHIPPING NAME	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport Hazard class	Class 2.1
Packing Group	Not Available

PRODUCT NAME Mullen Circle Brand, Inc.
Adams Elevator Waterproof Grease - Aerosol
Part# APA100CC-CASE, APA100S

******* SECTION XV – REGULATORY INFORMATION *******

TSCA Section 12(b) Export notification (40 CFR 707 Subpart D): None

CERCLA Hazardous Substance List (40 CFR 302.4): Acetone

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed

SARA Section 302 – Threshold Planning Quantity : None

SARA Title III – Section 311/312

Immediate/Acute Health Effects	: Yes
Fire Hazard	: Yes
Delayed/Chronic Health Effects	: No
Reactivity Hazard	: No
Sudden Release Of Pressure Hazard	: Yes

Chemical Release Reporting:

SARA Section 313	: Not listed
CERCLA	: Not listed

TSCA Inventory : All product ingredients are listed on the chemical inventory.

******* SECTION XVI – OTHER INFORMATION *******

The above mentioned information is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition the person receiving it shall make his own determination as to the suitability of the material for his particular use and on the condition he assume the risk of his use thereof.

Revision Date: August 1, 2016