

## SPECIFICATIONS

**0375-6**  
• 3/8" CLOSE QUARTER DRILL

CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT. LBS.	SHIP WGT. LBS.
0375-6	3/8"	120	3.5	0-1300	DOUBLE	1/2" - 20	48-66-2115	48-66-3240	6-1/2	3.0	3.5



**NEW**

**Lok-Tor™ SERIES**

**0616-24\* (KIT)**

- T-HANDLE DESIGN PROVIDES OPTIMUM BALANCE AND COMFORT
- 1/2" ALL METAL RATCHETING KEYLESS CHUCK



\* TOOL AVAILABLE WITHOUT BATTERY CHARGER OR CASE. SEE "O" MODELS IN SPEED CHART BELOW



**460 IN.-LBS. TORQUE!**

**NEW! ALL-METAL RATCHETING CHUCK WITH CARBIDE JAWS**



## SPECIFICATIONS

CATALOG NUMBER	VOLTS DC	SPEED RPM HIGH	SPEED RPM LOW	DRILL MAX. TO. IN.-LBS.	BATTERY CAPACITY A-HRS.	LENGTH INCHES	NET WGT. LBS.	SHIP WGT. LBS.
0616-24	14.4	0-1700	0-500	460	2.4	10-1/2	3.7	13.5

## SPECIFICATIONS



**0200-20**  
• WITH 3/8" KEYED CHUCK



CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT. LBS.	SHIP WGT. LBS.
0200-20	3/8"	120	7.0	0-1200	DOUBLE	1/2"-20	48-66-0806	48-66-3080	12	4.2	4.7

## SPECIFICATIONS

CATALOG NUMBER	SPEED RPM	DISC DIA.	VOLTS AC-DC	OUTPUT (WATTS/MAX HP)	AMPS	THREAD SIZE*	LENGTH (IN.)	WIDTH (IN.)	WGT. LBS.	WGT. LBS.
6148-6	10,000	4-1/2"	120	1200/1-2/3	8.5	5/8"-11	14	5	4.9	6.1

**6148-6**  
• 4- 1/2" SANDER/GRINDER WITH LOCK-ON



**NEW**

**48-59-0260**

• MULTI-BAY CHARGER



**JOB SITE TOUGH!**

### MULTI-BAY CHARGER 48-59-0260

- Charge Up To Three Battery Packs Of The Same Or Other Voltage Simultaneously
- Fast Charging In 45 Minutes For Minimal Down Time
- Micro-Controlled Conditioning Mode Maximizes Run Time Automatically During Each Charge Cycle
- Generator, Inverter And Long Extension Cord Ready - Due To Wide Input Voltage Range Of AC Charger
- Durable Construction Protects The Charger In Harsh Job Site Environment
- For Use With All Milwaukee Slide-On Style Battery Packs
- ② Dust Cover Protects Charger Terminals From Job Site Contamination and Debris
- ③ Automatically Retracts When A Battery Is Inserted
- ④ 9" Cord With Pass Through Plug
- ⑤ High Visibility LED Indicators Let You Know What Charging Stage The Battery Pack Is In
- Convenient Cord Wrap Also Acts As A Shock Absorber If The Unit Is Tipped Or Dropped
- Impact Resistant Base Provides Ultimate Protection In Job Site Conditions
- Withstands 8" Drop To Concrete (With Battery Packs Attached)

**5359-21**

- 1-1/8" CAPACITY
- 0-980 RPM
- CHIPPING MODE



- **D-Style Handle**  
Offers a secure grip that maximizes drilling pressure while minimizing operator fatigue.
- **Electronic Variable Speed Control Trigger**  
For smooth, controlled starts and hammering with rotation in concrete and masonry or drilling without hammering in wood or metal.
- **Slip Clutch**  
When bit jams, the clutch slips - rotary action stops.

### EXCLUSIVE 5362-6 FEATURE:

- **Reversing Switch**

## SPECIFICATIONS

CATALOG NUMBER	VOLTS AC ONLY	AMPS	RPM	REMOVEABLE SDS BIT HOLDER	BLOW ENERGY (FT.-LBS.)	BLOWS PER MIN.	SOLID BIT CAPACITY	WOOD FLAT BORING BIT	STEEL TWIST DRILL	CORE BIT CAPACITY	LENGTH INCHES	NET WGT. LBS.	SHIP WGT. LBS.
5359-21	120	7.4	0-980	NO	2.5	0-4200	1-1/8"	1-1/2"	1/2"	4"	13"	8.3	14.5