



Adams part no.	Description	Dimensions	Replaces Dover part nos.
DV55N4	Plunger/needle valve assembly for pilot solenoids	2 ⁵ / ₈ " L x 1 ³ / ₃₂ " x 1 ³ / ₃₂ "	9715060, P-56-43-1
DV55P1	Steel control piston for 63426 & 63431 UP pilot sections; use with DV55S3 control piston spring, below	1/2" O.D. x 1 ³ / ₄ " L	9730576, P-125-90
DV55P2	Delrin® orifice control piston for 63427 & 63432 DOWN pilot sections; use with DV55S4 orifice control piston spring, below	1/2" O.D. x 1 ⁵ / ₁₆ " L	9754076, 75407
DV55S1	Regulator spring for bypass sections & constant-speed lowering valves; 27 turns; use with DV55S2 spring seat washer, below	1 ¹ / ₁₆ " O.D. x 5 ³ / ₄ " L	9731143, P-150-24
DV55S2	Brass spring seat washer w/steel pivot ball; for DV55S1, above	Seat dimensions: 5/32" H x 2 ¹ / ₃₂ " dia.; Stem dimensions: 7/16" H x 1 ¹ / ₃₂ " dia.	9807524, P-149-7
DV55S3	Control piston spring for 63426 & 63431 UP pilot sections; 10 turns; use with DV55P1 steel control piston, above	7/16" O.D. x 1 ¹ / ₁₆ " L	9730590, P-125-92
DV55S4	Orifice control piston spring for 63427 & 63432 DOWN pilot sections; 28 turns; use with DV55P2 control piston, above	1/4" O.D. x 1 ³ / ₄ " L	9754064, 75406
DV55V1	Brass body NC solenoid seat for UP & DOWN pilot sections; incl. O-ring; use with DV55N4 plunger/needle valve ass'y., above	5/8" O.D. x 5/8" L	9788566, 28856
DV55V2	Steel body NO solenoid seat for 83426 & 63431 UP pilot sections; use with DV55N4 plunger/needle valve ass'y., above	5/8" O.D. x 5/8" L	9788554, 28855



Solenoid Coils with Covers

DV55C1 Solenoid coil in can with cover, 115VAC; 2 leads, for pilot solenoid; used with Dover part no. 9753965 NC and 9753977 NO solenoid valve assemblies.

Replaces Dover part no. 9755743.

DV55C2 Solenoid coil in can with cover, 115/230VAC, 70W, 4 leads.

Replaces Dover part nos. 9755895 and 9755883.



9731260
Solenoid
seat gasket



9832830
Check valve repair kit