


**G800B**  
Motor D00#1365B



The *G800B* replacement motor comes with only 2 armature leads. OEM-wound field motors (and our older G800A replacement) have 4 leads. Two fewer leads makes installation easier than ever. Connect only the A1 & A2 armature leads. Unused field leads can be taped off and ignored.



**G800C**  
Brush, for G800B  
(2 required)

DOOR MOTOR SPECIFICATIONS									
Adams part no.	Operating voltage	HP	Weight	No-load rpm	Motor type	Length		Diameter	
						Body	Shaft	Body	Shaft
<b>G800B</b>	230VDC	1/6	11.0 lbs.	1150	Perm. magnet	6 <sup>7</sup> / <sub>8</sub> "	1 <sup>5</sup> / <sub>8</sub> "	4 <sup>3</sup> / <sub>16</sub> "	5/8"



**GL-860-J**

MOTORS		
Adams part no.	Description	G.A.L. part no.
<b>GL-860-B</b>	MOTOR 1/4 HP 230 VDC, PM	MTR-0009N
<b>GL-860-C</b>	MOTOR 1/2 HP, 220 VDC, PM	MTR-0010N
<b>GL-860-J</b>	MOTOR 1/4 HP, 230 VDC, PM	MTR-0012N
<b>GL-860-Y</b>	MOTOR 1/4 HP, 115 VDC, 1150 RPM	MTR-0012N



**GL-915-H9**  
Motor Pulley



**GL-870-A**  
V-Belt 44"



**GL-870-B**  
Drive Belt 24"



**GL-942-B**



**GL-942-D**

SELECTOR PARTS		
Adams part no.	Description	G.A.L. part no.
<b>GL-942-B</b>	SELECTOR CONT INSULATOR	
<b>GL-942-C</b>	STATIONARY BRUSH HOLDER	SEL-0080N
<b>GL-942-D</b>	CONTACT BRUSH	SEL-0086N
<b>GL-942-E</b>	MOVABLE BRUSH HOLDER	SEL-0081N



**GL-942-C**



**GL-942-E**