

Door Operator Parts



| Adams part no. | Description | Haughton part no. |
|----------------|--|------------------------|
| J835 | Stationary contact assembly, complete; for "B" & "B1" contact assemblies and "J" limit switch. Used with J836 movable contact ass'y, below | 3-19237-02, 19237-C |
| J836 | Movable contact kit for "B" & "B1" contact assemblies and "J" limit switch; incl. contact mounted on 2 ³ / ₈ " x 1/2" insulator, and separate 2" x 1/2" insulator; used with J835 stationary contact assembly, above | 3-19239-01, 19239-A |



| Adams part no. | Description | Haughton part no. |
|----------------|--|------------------------|
| J830A1 | Bridge contact & bracket assembly (RH) for type "M" interlock; shown | — |
| J830A2 | Bridge contact & bracket assembly (LH) for type "M" interlock; opposite of shown | — |
| J831A1 | Bridge contact & bracket assembly (RH) for type "M" interlock; opposite of shown | — |
| J831A2 | Bridge contact & bracket assembly (LH) for type "M" interlock; shown | — |
| J20C1 | Brass bridge contact, used with J830A1/A2 assemblies, above | 3-28763-02, 28763-E |
| J22C3 | Heavy-duty bridge contact, used with J831A1/A2 assemblies, above | 3-28763-01 |
| J832B1 | Bridge contact bracket only (RH), for J830 & J831, above (shown) | 34-2551-004 |
| J832B2 | Bridge contact bracket only (LH), for J830 & J831, above (opposite of shown) | 34-2551-005 |



| Adams part no. | Description | Haughton part no. |
|----------------|---|------------------------|
| J820 | Door clutch roller, 2 ¹ / ₄ "OD x ⁹ / ₁₆ " wide face, ⁷ / ₁₆ " bore; for "T" and "TH" door operators | 3-16497-00, 16497-D |
| J825 | Interlock roller & pin assembly; polyurethane roller is 1 ³ / ₄ " dia. x ³ / ₄ " wide face; ⁵ / ₈ "-dia. axle is 1 ³ / ₈ "L | 35-2551-006 |
| J825R | Same as J825, without pin (not shown) | |



| Adams part no. | Description | Haughton part no. |
|----------------|--|------------------------|
| J840A | Moving contact assembly; incl. J840B insulator (below) and ³ / ₈ "-dia. silver contact; incl. J320 stationary contact; for type "K" limit switch | 3-20342-02, 20342-B |
| J840B | Insulator block for J840A moving contact ass'y., above; 1" x ³ / ₈ " x ³ / ₈ ", w/two 6-32 tapped holes | 34-1184-06 |
| A831 | Adams reel-type door closing spirator; universal mounting hub; heavy-duty construction, 5" dia. | 33-1651-001 |
| A832 | Standard-duty spirator, 5" dia. | 33-1651-001 |
| W832 | Spirator, 6" dia. | — |
| A831B | Mounting bracket for A831 and A832 spirators | — |