



Adams part no.	Description	Haughton part no.
J1	Forged copper contact; head: 1/2"L x 1 1/2"W x 1/2" thick; stem: 3/8" dia. x 1 3/4"L (threaded 1 1/2")	5736-B
J1C	Carbon contact for J1 copper; 1 1/2" x 1 1/2" x 3/4"	—
5737	Carbon contact 1 1/2" x 1 1/2" with copper base	—
J2	Forged copper contact; head: 1 3/4"L x 2"W x 1/2" thick; stem: 3/8" dia. x 2"L (threaded 1 3/4")	5574
J2C	Carbon contact for J2 copper; 1 3/4" x 2" x 3/4"	5575
J202	Copper finger, 3/32" thick x 1/2"W x 1 11/32"L; elongated mounting hole, 13/64"W x 7/16"L; cadmium plated	20324
J202B	Finger contact, 18 gauge stainless; 3/64" thick x 1/2"W x 1 9/32"L; elongated mounting hole, 13/64"W x 7/16"L	—
J20A1	Core bracket for armature assembly on AN & AM relays; use w/J20A2 & J20A3 armatures, below	3-28842-02, 28842-C
J20A2	Armature for AN, AM & BN 6-contact relays	3-28841-02, 28841-C
J20A3	Armature for AN, AM & BN 4-contact relays	3-28841-01, 28841-B



Adams part no.	Description	Haughton part no.
J20R1	Movable contact assembly for AN, AM & BN relays; contacts supplied 2NO/2NC (can be reconfigured in field to match job requirements)	3-10062-13
3-28763-02	Contact Bridge-Gold Contacts-for J20R1	3-28763-02
J20B1	Contact bridge guide (Bakelite) for J20R1	3-28764-02, 28764-B
J20B2	Contact bridge insulator for J20R1; Bakelite construction lasts longer, resists high temperatures	3-19487-03, 19487-C
J20C1	Contact bridge (brass) for J20R1; formed silver contact faces for outstanding wiping action (Also used on 10062-series movable contact assemblies and on J830A1/A2 interlocks)	3-40304-67
3-10062-02	Movable Contact Assembly-"F" type 2NO	3-10062-02
3-10062-03	Movable Contact Assembly-"F" type 1NO	3-10062-03
3-10062-04	Movable Contact Assembly-"F" type 1NC	3-10062-04
3-10062-08	Movable Contact Assembly-"F" type 2NC	3-10062-08
3-10062-09	Movable Contact Assembly-"F" type 1NC/1NO	3-10062-09
J20P1	Adjusting screw (not shown) for AN & AM relays; 1 1/16"L with 10-32 thread	3-17592-02, 17592-C
J20S1	Compression spring for J20R1, 1/2"OD x 3/4"L, 5 1/2 turns (Also used on 10062-series movable contact assemblies on AT & N relays)	22100
SH201	Stainless steel contact blade, 3/16"W x 1 1/16"L; incl. 1/8" dia. silver contact	—
SH202	Stainless steel contact blade, 3/8"W x 1 1/16"L; incl. 1/4" dia. silver contact	—
SH203	Stainless steel contact blade, 3/16"W x 2 3/4"L; incl. 1/16" dia. silver contact	—
SH204	Stainless steel contact blade, 5/16"W x 3 3/8"L; incl. 3/16" dia. silver contact	—
SH205	Stainless steel contact blade, 3/16"W x 1 1/16"L; incl. 5/32" dia. silver contact; 5° offset near midpoint	—



3-40340-17
Cam, vert.