



20918 Nylon door gib



P-15646
Cable ass'y,
4-cond. #18STR W



59666
Spacer



101295 Spacer,
25/64"ID x 1.438"OD



101161
Nyliner bushing
1/4"



90527-022
Door operator cable



P-31921-002



12936-00A
Pin, 3/8-24



19500-032
Pillow block, 3/4" bore



49115-003
Washer,
0.812"OD



101802
"E" ring, 3/8"



P-4232 Stationary
limit switch contact



101163
"E" ring, 3/16"



P-4231 Movable
contact



P-12926
Magnetic leveling
switch, 120VAC, 1.5A



61404
Photoelectric leveling sensor



101040
Retaining
ring



28974-1
Snap ring



20034 Nylon
clip



P-22177
Spacer &
bolt



101630
"S" hook,
5/16"ID



P-28319-00C
Limit switch,
replaced by
USP33217005



P-06388
Leveling switch
contacts



520770
Limit switch



P-16577
Low-voltage
level unit, 45VDC



19144
Damping motor,
1/2hp

M800A Door Motor



M800A. Permanent-magnet replacement for Montgomery 1/6-hp door motor.

M800C. Replacement brush, shown at right.



Replacement
brush for
M800A door motor.
Adams part no. M800C



P-12861
Limit switch, 6
steps



P-01046-00C
Gate switch, replaced by
USP1046001

DOOR MOTOR SPECIFICATIONS

Adams part no.	Operating voltage	HP	Weight No-load	rpm Length	Motor type	Length		Body		OEM part no.
						Shaft	Diameter	Shaft	Diameter	
M800A	24VDC	1/6	7.8 lbs.	1140	Perm. magnet	6 ⁵ / ₁₆ "	1 ¹ / ₂ "	3 ³ / ₁₆ "	1/2"	101849

Magnetic Leveling Switch

M3000. Magnetic leveling switch in aluminum housing. Wires are red & black. 24VDC, 2N/O

