

"S" in part nos. is your key to the quietest-running polyurethane guide rollers around!

**O420S
O420**

**O421S
O421
Permanent
Lube!**

O425

NOTE: O421 and O423 are same size. Perspective of picture has distorted size.

O422S

**O423
O423S
Permanent
Lube!**

**O421X
bolt & bushing**

Adams part no.	Description	Dimensions		Materials		Otis part no.
		Dia.	Width	Hub	Tire	
O420S	Roller guide wheel with axle shaft for 6261A roller guide assembly	3 ³ / ₄ "	1 ¹ / ₈ "	Aluminum	SPx ⁸⁰ ™	456AK2-SV
O420					HDx ⁹⁵ ™	456AK2
O421S	Roller guide wheel for 6261C roller guide assembly, 1941 thru 1962; permanent lube	7 ⁷ / ₈ "	1 ¹ / ₂ "	Die-cast aluminum	SPx ⁸⁰ ™	456AJ2 -SV
O421					HDx ⁹⁵ ™	456AJ2
O422S	Guide roller with axle shaft, for 6261P roller guide assembly; w/pump shaft bearing	3 ³ / ₄ "	1"	Die-cast aluminum	SPx ⁸⁰ ™	456CN4-SV
O422	Guide roller with axle shaft, for 6261P roller guide assembly; w/pump shaft bearing	3 ³ / ₄ "	1"	Die-cast aluminum	HDx ⁹⁵ ™	456CN4
O423S	Roller guide wheel w/axle shaft; used on 6261C guide assy, after Dec 62; perm. lube	7 ⁷ / ₈ "	1 ¹ / ₂ "	Die-cast aluminum	SPx ⁸⁰ ™	456CL4-SV
O423					HDx ⁹⁵ ™	456CL4
O424S	Roller guide wheel with axle shaft enclosed by pump shaft bearing; used for 6261H roller guide assembly	4 ⁷ / ₈ "	1 ¹ / ₈ "	Die-cast aluminum	SPx ⁸⁰ ™	456CM4-SV
O424P					Rubber	456CM4
O425					HDx ⁹⁵ ™	456CM4
O425	Roller guide wheel with axle shaft enclosed by pump shaft bearing; used on 6261T roller guide assembly	10"	1 ¹ / ₂ "	Die-cast aluminum	Rubber	456CV4

O421X. Lever arm bolt & bushing for **O421** and **O423** guide rollers; hardened steel bushing with hardened cold-rolled steel pin. 3" long, with shaft diameter of 3/4". See photo inset, above. Replaces Otis part nos. 59P1 and 335H1. Bushing has an Outside Diameter of 1.002".

COLOR KEY FOR ADAMS POLY

Red = LF⁸⁰ Low Friction
Black = SP⁸⁰ Soft
Clear = HD⁹⁵ Heavy Duty