

TRIPLETT SPECIALTY TESTERS

A106PT6 ProTemp 6 Non-Contact, Infrared Thermometer



- ▲ 6:1 Measurement Ratio
- ▲ Streamlined, Ergonomically Styled Case
- ▲ Cool Blue Backlit Display
- ▲ Non-Slip Finger Treads
- ▲ Not "Gun Shaped" like competitors models
- ▲ Laser Pointer pinpoints center of measurement area
- ▲ Simple, One-Button Operation
- ▲ 0° to 605° F (-18° to 315° C)
- ▲ User Selectable ° F or ° C Display
- ▲ Holds Reading Automatically for 7 Seconds
- ▲ Auto Power Off
- ▲ Fixed Emissivity (0.95)
- ▲ Battery Level Indicator
- ▲ Operates from a standard 9 Volt Battery
- ▲ One Year Warranty

Specifications

Temperature Range:	0° to 605° F (-18° to 315° C)
Operating Temperature:	50° to 125° F (10° to 52° C)
Resolution:	1° F (1° C)
Accuracy:	77° to 500° F (25° to 260° C) ± 2% of reading or 3° F (2° C) plus one digit, whichever is greater
	30° to 76° F (0° to 24° C) ± 3% of reading or 5° F (3° C)
	0° to 29° F (-18° to -1° C) ± 4% of reading or 7° F (4° C)
Response Time:	500 mSec, 95% Response
Target Size/Field of View:	6:1 optics ratio with a 1" minimum target
Repeatability:	2% of reading, or 3° F (2° C)
Spectral Response:	7-18 um
Emissivity:	Fixed at 0.95
Relative Humidity:	10-95% RH noncondensing, @ up to 86° F (30° C)
Storage Temperature:	-4° F to 150° F (-20° to 65° C) without battery
Battery:	1 - 9 volt Alkaline Battery
Battery Life:	12 Hours Continuous Operation
Dimensions:	7.25" x 1.75" x 1.5"
Weight:	4.8 oz.

Triplett: Model ProTemp 6



A106TDR Triplett TDR Cable Fault Finder

- ▲ Find Cable Length or Distance to Fault from ONE END!
- ▲ Low Cost Digital Cable Length Meter/TDR
- ▲ Built-in Tone Generator for Cable Tracing & Identification
- ▲ Simple Operation with Automatic Distance Display
- ▲ Internal Library of 39 Standard Cable Types
- ▲ Suitable for testing all types of Communication Cables
- ▲ Compact, Ergonomic Design, weighs less than 8 oz.
- ▲ Padded Cordura Holster included
- ▲ Three Year Warranty

Triplett TDR

Triplett TDR Specifications:
Approximate Range:

Resolution:	Coaxial Cable 6400 ft
Accuracy:	Structured Wiring 2500 ft
	Telephone Cable 2500 ft
	1 ft < 300 ft & 3 ft > 300 ft
	± 2 feet - Cables up to 10 ft
	± 5 feet - Cables 10 to 200 ft
	± 3% - Cables longer than 200 ft
Cable Library:	39 Standard Cable Types
Output Impedance:	50, 75 & 100 Ohms
Velocity of Propagation:	Adjustable 0 to 99%
Tone Generator:	Oscillating 810 - 1110Hz
Display:	Dot Matrix LCD

Connector Type:	BNC
Power Supply:	1 - 9 Volt Battery
Battery Life:	Approx. 2000 Tests
Operating Temperature:	5 to 122 deg. F
Storage Temperature:	-4 to 158 deg. F
Dimensions:	8 x 3 x 1.5 inches
Weight:	8 oz.
Safety:	IEC61010-1, EN 60950
EMC:	BS/EN 61326-1
Includes:	Padded Cordura Holster, Test Lead, Adaptor w/ Alligator Clip, 9V Battery



A106FOX The Original Fox Tone Generator



- ▲ Generates 3 distinct tones usable for wire tracing
- ▲ Performs a variety of tests on telephone lines
- ▲ Line powered in Tone Mode
- ▲ LED Indicator for continuity
- ▲ Supplies "Talk Power" to allow communicating between handsets (talksets) or powering a telephone
- ▲ Alligator clips and modular plug allow for connection to stripped wires, terminal panels, or a standard modular jack (single line)
- ▲ Powered by a standard 9V battery (not included)
- ▲ Works with Hound, Hound 2 or Hound 3 Probe Inductive Tracers
- ▲ One Year Warranty

Triplett: Fox

A106 Hound The Hound 3 Probe Streamlined Inductive Tracer with Headlights and Earphone Jack



- ▲ New Headlights to help light your way in dark areas and reduce florescent light noise
- ▲ Streamlined Design allows for better access in hard-to-reach areas
- ▲ New Shielded Design to suppress "Feedback Squeal"
- ▲ Bandpass Filter to suppress 60Hz and Hi Frequency Noise
- ▲ Earphone Jack for use in quiet or noisy environments.
- ▲ Improved Sensitivity and Loudness
- ▲ Includes New Conductive Duck-Bill Tip for Safer, Easier Penetration in cable bundles - Metal tip also included
- ▲ Easy Access Battery Door
- ▲ Adjustable volume / sensitivity control
- ▲ LED gets brighter as the signal gets stronger - LED indication even works when Earphones are used!
- ▲ Contains a hi-gain, hi-impedance amplifier
- ▲ Capable of identifying the Fox's tone up to 12 inches away
- ▲ Rugged, moisture resistant, mylar cone speaker
- ▲ Use with the Fox 2, Fox, TDR or WireMaster XR-2 for quick & efficient wire tracing
- ▲ Powered by a standard 9V battery (not included)
- ▲ One Year Warranty

Triplett: Hound 3

A724H3 Fox & Hound 3 Probe Kit



Includes:

- ▲ Original Fox Tone Generator
- ▲ Hound 3 Probe Inductive Tracer
- ▲ Cordura Carrying Case

Triplett: Cat No. 3397