


### SPROCKETS FOR DOOR SYSTEMS



**195AT2**  
Otis  
Sprocket



**195CH2**  
Otis  
Sprocket  
12 teeth  
1.56" O.D.  
for 6850A, B, C



**195CP2**  
Otis  
Sprocket  
9 teeth 1.25" O.D.  
.75" W  
.325" I.D.  
Used on 305 Operator



**195GK2**  
Otis  
Sprocket  
.626 I.D.  
10 teeth  
Used on 7300A,AA

### SHEAVES AND ROPES



**251BT3**  
Otis  
Sheave Rope



**265BC2**  
Otis  
Sheave  
5" diameter



**265BD2**  
Otis  
Sheave  
2 5/8" diameter

SHEAVE ROPES	
Part No.	Description
<b>251BT3</b>	27" Drive Sheave, 1/2" Treaded Rope
<b>251BT5</b>	30" Drive Sheave, 1/2" Treaded Rope
<b>251BV1</b>	32" Drive Sheave, 5/8" Treaded Rope
<b>251BV5</b>	28" Drive Sheave, 5/8" Treaded Rope

### MISCELLANEOUS BUSHINGS



**335E22**  
Otis  
Oil lite Bushing



**335E86**  
Otis  
Oil Lite Bushing



**321CJ4**  
Otis  
Bushing



**128AG61**  
Otis  
Washer 1.50" O.D.,  
1.00" I.D., .016" Thk.



**334C1**  
Otis  
Bushing



**335E84**  
Otis  
Oil Lite Bushing

BUSHINGS				
Part No.	O.D.	I.D.	Length	Flange
<b>321CJ4</b>	1.475"	.75"	1.12"	.188" dia.
<b>321CJ3</b>	1.398"	.75"	1.13"	.188" dia.
<b>212T4</b>	1.13"	1.00"	1.00"	n/a
<b>335E22</b>	1.25"	1.00"	0.75"	n/a
<b>335E84</b>	0.88"	0.75"	1.12"	n/a
<b>335E86</b>	0.63"	0.50"	0.37"	n/a
<b>335H7</b>	.75"	.50"	.62"	.88" dia.
<b>335H12</b>	.68"	.50"	.63"	.88" dia.

\*212T4 Used on R Governor