



**MOTOR BEARINGS**

All bearings from Adams are cast for superior strength and rigidity. Cast bearings withstand temperature and pressure better than their

forged counterparts or those machined from bar stock. For long life and reliability, cast bearings should be your first choice.

BRONZE SLEEVE MOTOR BEARINGS					
Adams part no.	Otis casting	Bore	Length	Motor no.	Otis part no.
<b>O600</b>	R-2671	2"	5"	5 & 7½ AC	151357, 121932, 132347
<b>O601</b>	R-2675	2¼"	5¾"	10, 15, 17 AC	151358, 121919, 132346
<b>O602</b>	R-2676	2¾"	6⅞"	20 to 35 AC	151359, 18742, 122236
<b>O604</b>	R-2963	2"	5"	3½, 4, 4½ S	151354, 101319, 132348
<b>O605</b>	R-3110	2⅞"	5⅜"	5½ S & A-S	151355, 101322, 132349
<b>O612</b>	R-2964	1⅞"	3½"	1¼ S, 1½ S, 2½ AC	151352
<b>O613</b>	—	2"	3¾"	71GA, 77G, 83 ES	210R1

BABBITTED MOTOR BEARINGS				
Adams part no.	Bore	Length	Description	Otis part no.
<b>O608</b>	2⅜"	5¼"	Babbitted bearing for 1A/1B MG, 89F motor	Old #1215MO-1; 210AA1 (supercedes 140694)
<b>O609</b>	2⅜"	6"	Babbitted bearing for 2A/2B, 3A, 4AMG, 98G, 112G sets	Old #1084MO-1; 210BA1 (supercedes 138109)

NOTE: Babbitted motor bearings are iron castings sealed and shipped in oil to protect against rust.

**MACHINE PACKING**



Adams part no.	Diameter		Packing length	Otis part no.
	Worm shaft	Packing space		
<b>O692</b>	1⅝"	2⅞"	1⅜"	182A2
<b>O693</b>	1⅞"	2⅞"	1⅞"	182A3
<b>O694</b>	1⅞"	3⅞"	2⅞"	182A4
<b>O695</b>	2⅞"	3⅞"	2⅞"	182A5
<b>O696</b>	2¼"	3½"	2"	182A6
<b>O697</b>	1⅞"	2⅞"	1"	182A14
<b>O698</b>	1⅞"	2⅞"	1¼"	182A15
<b>O699</b>	1⅞"	3"	2⅞"	182A18

**MISCELLANEOUS SEALS**



**33AA2**  
Otis  
Oil Seal-Solid



**182A5**  
Otis  
Packing



**182A17**  
Otis  
Packing



**182C1**  
Otis  
Packing



**33D14**  
Otis  
Oil Seal 2.250" O.D.