

NEW **HydroCool™**



HydroCool™ is perfect for any hydraulic elevator with high usage

Other recommended applications include:

- Twin jack holeless applications with two- or three-stage telescopic jacks
- Heavily used single-stage twin jack holeless projects
- Roped hydraulic applications with moderate usage and travel exceeding 25 feet

Compact, adaptable HydroCool works with all power units!

Technical Data: HydroCool™

Operation	Adjustable thermostat control. Separate pump and fan motors.
Cooling Capacity	17,500 BTU/hr
Pump Capacity	8 gallons per minute
Power Requirements	Provide 120 VAC, 20A circuit
Size	28"H x 24"W x 17.5"D
Weight	Approx. 140 lbs.
Mounting Options	Can be mounted up to 110 feet horizontally or 55 feet vertically from the power unit.*

HydroCool — Reg. TM Adams Elevator Equipment Company
*Piping, wiring and conduit to remote location are not included.

HydroCool II™

Technical Data: HydroCool II™

Operation	Starts automatically at 140°F; Shuts off at 100°F. Single motor drives fan and pump.
Cooling Capacity	12,000 BTU/hr
Pump Capacity	3 gallons per minute
Power Requirements	Provide 120 VAC, 20A circuit; Fan motor FLA 3.4; Pump motor FLA 6.6
Size	20.5"H x 26"W x 26"D
Weight	Approx. 125 lbs.
Mounting Options	Adjacent to reservoir only

Economical solution for less frequently-used hydraulic elevators

HydroCool II™ maintains oil quality and integrity by pumping oil through a heat exchanger where it is cooled and returned to the oil storage tank. Package includes preassembled fan/pump/heat exchanger unit, hoses and mounting brackets.



HydroCool II — Reg. TM Adams Elevator Equipment Company

NEW **Pully Bully**

Pully Bully

Use Pully Bully for changing a submersible pump or motor. The Pully Bully is safe, light weight and portable. Comes complete with drip pan for easy clean-up. Saves time with quick and easy set up. Safe to use. Comes with portable cart.

Specifications:
Lifts up to 500 lbs
Weighs 185 lbs
Complies with ASME B30.17 - 1998

HYDROCOOL™ AND PULLY BULLY ORDERING INFORMATION

Adams part no.	Description
A900A	HYDRAULIC OIL COOLER ASSEMBLY (Includes all fittings and hardware needed for adjacent-mount installation. Piping, wiring and conduit to remove location not included.)
A900B	MOTOR PUMP ONLY FOR OIL COOLER A900A
A900C	PULLY BULLY WITH CART (for hoisting submersible pumps or motors)

NEW