



CONTACT ASSEMBLIES

Adams part no.	Description	Westinghouse part no.
W210S1	For KS multipole relay and 15A contactor; incl. 6 ¹ / ₄ "L shunt and 1 ¹ / ₄ " dia. silver contact	M1230-G6
W210S2	Same as above, with 5 ¹ / ₄ "L shunt	M1230-G5
W210S3	Same as above, with 4 ³ / ₄ "L shunt	M1230-G4
W211	For 30VS relay and 15A contactor; 1 ¹ / ₄ "L x 1 ¹ / ₂ "W plus 7"L shunt; no silver contact	K181G2, G3
W212	For DS relay; incl. 7 ¹ / ₁₆ " dia. silver contact face; 1 ¹ / ₄ "L x 1 ¹ / ₂ "W plus 7"L shunt; makes with W221 stationary contact and W58 contact	M3466-G01
W213	Copper base 1 ⁵ / ₈ "L x 1 ¹ / ₂ "W; incl. 2-strand bare copper shunt, 4 ¹ / ₂ "L w/1 ¹ / ₄ " ID eyelet terminal	K-180 series
W214	Copper base 2 ¹ / ₂ "L x 5 ⁵ / ₈ "W; incl. 6"L fabric-covered shunt w/3 ¹ / ₁₆ " ID eyelet terminal	K180-G5 T3534G8
W215A1	"Make" assembly w/6 ³ / ₄ "L shunt (W217S3)	M4522G2, G3
W215A2	"Break" assembly w/6 ³ / ₄ "L shunt (W217S3)	M4522G5
W215A3	"Make" assembly w/1 ¹ / ₈ "L shunt (W217S2)	M4522G1
W215A4	"Break" assembly w/1 ¹ / ₈ "L shunt (W217S2)	M4522G4, G6
W216C1	Contact, "makes" with W50, W50C & W50CX carbons; for W215A1, A3	K-4278-G1 630B610G01
W216C2	Contact, "breaks" with W50, W50C & W50CX carbons; for W215A2, A4	K-4278G2 630B610G02
W217S2	Shunt w/eyelet terminals, 1 ¹ / ₈ "L center to center; for W215A3, A4 contact assemblies	X22G-G2
W217S3	Shunt w/eyelet terminals, 6 ³ / ₄ "L center to center; for W215A1, A2 contact assemblies	X22G-G3, G4

STATIONARY & MOVABLE CONTACTS

Adams part no.	Description	Westinghouse part no.
W218	Heart-shaped movable contact for 6B, CR and TC Relays.	K4277G01
W218A	Same as W218, with heavy-duty spring for 2X contact pressure	K4277G02
W219	Stationary contact for 6B and CR relays; 2 ⁷ / ₈ "L inside "U"; incl. threaded mounting stake & 1 ¹ / ₄ " dia. silver contact; "makes" with W218, W218A	X24AS1G04
W219L1	Stationary contact for 6B, CR & TC relays; incl. threaded mounting stake and 1 ¹ / ₄ " dia. silver contact; 3 ¹ / ₁₆ "L outside "U", contact outside	X24AS1-G01
W219L2	Same as above, 3 ³ / ₄ "L inside "U", contact inside	X24BS1-G01
W219L3	Same as above, 3 ³ / ₃₂ "L inside "U", contact inside	X24BS1-G02, G04
W219L4	Same as above, 4 ³ / ₈ "L inside "U", contact outside	X24AS1-G05
W219L5	Same as above, 3 ¹ / ₁₆ "L inside "U", contact outside	X24AS1-G06
W220	Stationary contact for KS, 15A, V VR, & 30V relays; 1 ¹ / ₈ "L overall with 1 ¹ / ₄ " dia. silver contact	M-1230-G3 M-1230-G23
W221	Stationary contact for DS relay; 1 ¹ / ₈ "L overall with 7 ¹ / ₁₆ " dia. silver contact	M-1230-G20
W201	Contact finger for Type SW interlock; 3 ⁵ / ₈ "L	K3125-G1
W202	Contact finger for Type SW interlock; 3"L	K3125-G2
W203	Contact finger for Type SW interlock; 3 ¹ / ₂ "L	K3125-G3
W204	Contact finger for Type SW interlock; 4 ³ / ₁₆ "L	K3125-G4