



AP010GC **AP020GC** **AP0440GC** **AP0900GC**



APA150CC
APA160CC **AP0900QC** **AP0800QC** **AP050G**

Buffer Oil. For applications that require protection against rust and oxidation, but do not require anti-wear or extreme-pressure additives. Use for lightly-loaded plain and anti-friction bearings, electric motors, machine tools, air compressors, and circulating systems.

ISO #32: Used in moderate-load shock-absorbing devices. Low volatility reduces oil consumption, and prevents pressure build up.

ISO #68: For severe services where heavy continuous loading is common.

AP020GC Buffer Oil, ISO #32. 1-gallon bottle, 4 gallons/case only.

AP010GC Buffer Oil, ISO #68. 1-gallon bottle, 4 gallons/case only.

Door Closer Oil. Designed to lubricate and protect high-speed spindle bearings. Also used wherever an ISO 10 rust- and oxidation-inhibited hydraulic oil is specified.

Separates rapidly from water; hydrolytically stable. Provides excellent friction, filterability, rust and corrosion protection properties, as well as superior thermal and oxidative stability.

AP0440GC Door Closer Oil. 1-gallon bottle, 4 gallons/case only.

Brake Oil. This is a high-dielectric, highly-defined oil with a very low pour point.

AP0900GC Brake Oil, 1-gallon bottle, 4 gallons/case only.

Light Penetrating Oil is an excellent general-purpose aerosol lubricant for use in the shop and at the job site. Use as both a general lubricant and short-term rust inhibitor. Clean formula contains no excess graphite, molybdenum disulfide, etc.

APA160CC Light Penetrating Oil. 16-oz. aerosol can, 6 cans/case only.

Heavy-Duty Penetrating Oil is a penetrating aerosol catalyst that breaks through rusted joints and pipe threads with "capillary wet drilling action." Releases rusty, sticky, gummy, and frozen joints in any temperature. Displaces moisture...even starts engines!

APA150CC Heavy-Duty Penetrating Oil. 16-oz. aerosol can, 6 cans/case only.

Elevator Oil Refresher. This blend of plant extracts neutralizes hydraulic oil odors with its mild wintergreen fragrance. Use one quart per 50 gallons of hydraulic oil...more if necessary. Compatible with petroleum oils and additives found in hydraulic systems.

AP0900QC Elevator Oil Refresher. 32-oz. bottle, 12 quarts/case

Soft Stop "Anti-Chatter" Additive. This performance-improving fluid is a special friction modifier that enhances the flow characteristics of most hydraulic systems. It can relieve the "stick-slip" problem on noisy hydraulic cylinders. Not recommended for machines with common systems for hydraulic, transmission, and braking.

AP0800QC Adams Soft Stop Hydraulic Additive. 32-oz. bottle, 12 quarts/case only.

Non-Dripping Oil. This unique lubricant features ideas borrowed from several disciplines. Designed as a super penetrant and lubricant, it will not drip from chains, guides, or cables over areas where pedestrians will be concentrated.

It is non-corrosive to steel, brass, aluminum, and common plastics such as polypropylene, nylon, and PVC. Cleans contacted parts to insure proper lubrication and freedom of movement. For heavily-soiled or gummed parts, repeat applications or soaking may be necessary. Relatively high flash point and mild hazard profile.

AP050G Non-Dripping Oil. 4 gal./case.