

**Please Print!** Survey must be fully completed and dated for order processing. Ship to: Job \_\_\_ or Shop \_\_\_ (check one)

Job Name \_\_\_\_\_

Code in Force (i.e. A17, Title 8, B44) \_\_\_\_\_

Job Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip/Postal Code \_\_\_\_\_ Country \_\_\_\_\_

Car # \_\_\_\_\_ Number of Landings \_\_\_\_\_ Travel \_\_\_\_\_ ft Pit Depth \_\_\_\_\_ ft Car Speed: \_\_\_\_\_ fpm.

Jack Mfg. \_\_\_\_\_ Plunger Wall Thickness \_\_\_\_\_ inches Capacity of Car \_\_\_\_\_ lbs. Car Weight \_\_\_\_\_ lbs.

Original Elevator Installing Company: \_\_\_\_\_ Date of installation \_\_\_\_\_ Mfg.'s Job Number \_\_\_\_\_

Include LifeJacket Information Display Option LJ4050 (additional charge applies): \_\_\_ Yes \_\_\_ No (*Required in Michigan*)

Packing, specify style and size \_\_\_\_\_ **Packing Must be Replaced** Is Controller: \_\_\_ Solid State OR \_\_\_ Relay

Is Pit prone to flooding? Yes \_\_\_ No \_\_\_ - - - - - (if yes, NEMA 3R conduit [liquitite flex] is supplied)

Does elevator have a bottom final limit switch? Yes \_\_\_ No \_\_\_ - - - (if yes, it must open prior to buffer engagement)

Does Cylinder have a tapped bleeder hole in the head? Yes \_\_\_ No \_\_\_ - - - (if no, optional drill and tap is supplied)

Is 120VAC available in controller? Yes \_\_\_ No \_\_\_ - - - - - (if no, 480/240 to 120 transformer is supplied)

How many 'wiring' feet from controller to Cylinder head? \_\_\_ Ft - - - (length of shielded cable sent for set coils and encoder)

Special delivery instructions (e.g., Do you have a forklift to get it off the truck?) \_\_\_\_\_

**Pit Information Record dimensions to 3 decimal places (i.e. 1.234). DO NOT USE FRACTIONS**

**The plunger diameter (PD) must be accurately measured to thousandths of an inch. Using a diameter tape, measure the plunger in at least three (3) places. Record these measurements in the blanks below. Start measurements a foot or so above the packing head.**

(PD) 1 \_\_\_\_\_. 2 \_\_\_\_\_. 3 \_\_\_\_\_. 4 \_\_\_\_\_

**See diagrams on page 2 for graphic illustration of dimensions. These dimensions must be accurate for proper fit. All dimensions below must be in inches.**

(BSD) \_\_\_\_\_" (UFD) \_\_\_\_\_" (FD) \_\_\_\_\_" (CD) \_\_\_\_\_" (BN) \_\_\_\_\_"  
*Buffer spring diameter Upper Flange Diameter Flange Diameter Cylinder Diameter Number of Buffer springs*  
\*cannot exceed 17" dia.

(RB) \_\_\_\_\_" (BS) \_\_\_\_\_" (SD) \_\_\_\_\_" (BB) \_\_\_\_\_"  
*Runby Buffer Stroke Strike Distance Between Buffers distance*

(CHF) \_\_\_\_\_" (CHC) \_\_\_\_\_"  (LifeJacket legs are made to CHF height unless checked here)  
*Top of cylinder to top of footer Top of cylinder to floor*

**Company** \_\_\_\_\_ **Address** \_\_\_\_\_

**City** \_\_\_\_\_ **State** \_\_\_\_\_ **Zip/Postal Code** \_\_\_\_\_

**Survey completed by** \_\_\_\_\_ **Date** \_\_\_\_\_

**PO #** \_\_\_\_\_ **Charge #** \_\_\_\_\_ **Adams Order #** \_\_\_\_\_

**Phone #** \_\_\_\_\_ - \_\_\_\_\_ **Fax #** \_\_\_\_\_ - \_\_\_\_\_ **Serial #** \_\_\_\_\_