

ESCUTCHEONS

Door sleeves. Available in two designs. Each standard escutcheon is supplied with one (1) push-nut. The "Tuff-Nut" escutcheon features oversized dimensions, 1" of exterior thread and is supplied with a threaded flat washer nut. All Escutcheons have an I.D. hole diameter to fit a 3/8" key.



ES15SS



ES15YB



ES15AL



ES20SS



ES20YB



ES20AL



ES27SS



ES27YB



ES27AL



ET15YB



ET20YB



ET20AL

Adams part no.	Description
ES15SS	Escutcheon, std. door sleeve, 1.5"L x 0.5" dia., Lip = 0.625" dia. - Stainless Steel
ES15YB	Escutcheon, std. door sleeve, 1.5"L x 0.5" dia., Lip = 0.625" dia. - Brass
ES15AL	Escutcheon, std. door sleeve, 1.5"L x 0.5" dia., Lip = 0.625" dia. - Aluminum
ES20SS	Escutcheon, std. door sleeve, 2.0"L x 0.5" dia., Lip = 0.625" dia. - Stainless Steel
ES20YB	Escutcheon, std. door sleeve, 2.0"L x 0.5" dia., Lip = 0.625" dia. - Brass
ES20AL	Escutcheon, std. door sleeve, 2.0"L x 0.5" dia., Lip = 0.625" dia. - Aluminum
ES27SS	Escutcheon, std. door sleeve, 2.75"L x 0.5" dia., Lip = 0.625" dia. - Stainless Steel
ES27YB	Escutcheon, std. door sleeve, 2.75"L x 0.5" dia., Lip = 0.625" dia. - Brass
ES27AL	Escutcheon, std. door sleeve, 2.75"L x 0.5" dia., Lip = 0.625" dia. - Aluminum
ET15YB	Escutcheon, tuff-nut door sleeve, 1.5"L x 0.625" dia., Lip = 0.875" - Brass
ET15AL	Escutcheon, tuff-nut door sleeve, 1.5"L x 0.625" dia., Lip = 0.875" - Aluminum
ET20YB	Escutcheon, tuff-nut door sleeve, 2.0"L x 0.625" dia., Lip = 0.875" - Brass
ET20AL	Escutcheon, tuff-nut door sleeve, 2.0"L x 0.625" dia., Lip = 0.875" - Aluminum